

## Drilling Unit AB 4600





### Range of application

- Blast hole drillings

### High performance device in the quarry for excavators >25 tons

- for efficient hammer drilling
- Rod changer single/3-/5-fold available
- Light and stable high performance profile
- Large standard equipment package, many additional options



# Technical Details AB 4600

	AB 4600 T-510	AB 4600 T-710
<b>Drill Hammer</b>	WHL 510	WHL 710
<b>Weight (kg)</b>	ca. 2100	ca. 2300
<b>Drilling diameter max. (mm)</b>	89	115
<b>Torque (Nm)</b>	625	1095
<b>Drilling unit - shenk adapters</b>		
<b>Blasthole drilling</b>	R32, T38, T45	R38 / T45 / T51
<b>Rod length (mm)</b>	3660	3660
<b>Total length (mm)</b>	6430	6430
<b>Oil supply (L/min)</b>	170 @ 170 bar	230 @ 200 bar
<b>Required motor performance (kW)</b>	60	96
<b>Oil pressure @excavator (bar)</b>	200	230
<b>Carrier to</b>	> 25	> 25
<b>Execution</b>		
<b>Feed shift (mm)</b>	1180	1180



## Options for all systems

- Clamp breaking device
- Angle indication
- Dust collector
- Compressor on the excavator
- PLC automatic
- Wimmer Cockpit
- Reinforced feed
- Single/3-/5-fold rod changer

## Standard equipment

- ✓ Rod clamping device
- ✓ Hose roller
- ✓ 360° endlessly rotatable, 90° tiltable
- ✓ independant electric power supply
- ✓ Radio remote control - all drilling functions proportionally controlled
- ✓ Blank firing protection
- ✓ Anti-jamming automation
- ✓ Hollow protection

WIMMER Hartstahl GmbH & Co KG und WIMMER Felstechnik GmbH  
 Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel. +43 (0)6235 6655-0

office@wimmer.info

[www.wimmer.info](http://www.wimmer.info)

